interstuhl

Technical data sheet 17V2

Specification Office swivel chair medium high, seat a. back uphol

| Dimensions in mm | Backrest: | H: | 520 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 400-525 |
| | | W: | 500 |
| | | D: | 520 |
| | Total: | H: | 1140 |
| | | W (no ArmR): | 545 |
| | | W (ArmR): | 600 |
| | | D: | 610 |
| Packaging data | Weight: | kg | 19,5 |
| | Volume: | m³ | 0,65 |
| | | | |



| Basic equipment | | Benefit |
|------------------------|---|---|
| Backrest | Back medium high, upholstered 30 mm foam. | Great seating comfort due to the ergonomically designed backrest. |
| Upholstery | Seat upholstered. Breath actively moulding foam, CFC - CHC - free (segregated foam). Seat 35 mm foam + 10 mm cotton. | Paddings are unglued, ensuring optimal air movement, breathable. |
| Mechanism | Smart Motion Technology, lockable in 4 positions. Opening angle between seat and back up to 110°. | The perfectly kinematic movement of the Smart Motion Technology encourages the user to change seating position frequently; in addition, the active seat inclination supports an ergonomic position especially when working at the desk. |
| Seat height adjustment | Seat height adjustment infinitely variable from 400 - 525 mm. Self-supporting safety gas spring. | Even people outside the DIN range (i.e. taller than 192cm and smaller than 151cm) will sit in the most ergonomic way. |
| Seat depth adjustment | Sliding seat for individual seat depth adjustment. Can be adjusted by 70 mm. | The real support area for the thighs of taller people will be enlarged. |
| Seat inclination | Flexible adaption to users movements forward +2° and backward -5°, lockable. | The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column. |
| Weight Adjustment | From 45 - 130kg, adjustable per ratchet element in 10 levels | Individual adjustment of the backrest and the back pressure to the weight and height of the user. |
| Castors | Hard castors, load-dependent braked, for soft floors (according to DIN EN 12529). | The chair does not roll away in an off-loaded situation, minimum risk of accident. |
| Base | Aluminium base, black. | Very high stability, long service life. |
| Materials | All materials are segregated and recyclable. | Environmentally friendly. |
| Standards | EN 1335 for office swivel chairs and office swivel armchairs. GS-symbol for having tested safety, tested for contaminants and ergonomics. | High quality product and great comfort. |

interstuhl

Technical data sheet 17V2

Specification Office swivel chair medium high, seat a. back uphol

| Warranty and return | | 10 years warran recycling guaran | ty. Complete return and tee. | Exchange of parts free of charge within the guarante period. |
|---------------------|-----------|--|---|--|
| | | Environmental n ISO 14001:2009 Commitment to s | anagement system DIN EN 0. OHSAS, EcoVadis gold, sustainability. Quality Office, na e3 level Platin. | |
| Certification | | Quality management system DIN EN ISO 9001:2008, VO (EG) Nr. 1221/2009 (EMAS), | | High quality product. |
| | | | | |
| | Volume: | m³ | 0,65 | |
| Packaging data | Weight: | kg | 19,5 | |
| | | D: | 610 | |
| | | W (ArmR): | 600 | |
| | | W (no ArmR): | 545 | |
| | Total: | H: | 1140 | |
| | | D: | 520 | |
| | | W: | 500 | |
| | Seat: | H: | 400-525 | |
| Dimensions in mm | Backrest: | H: | 520 | |

Disassembly instructions are available upon request for any interstuhl product

interstuhl

Technical data sheet 17V2

Specification Office swivel chair medium high, seat a. back uphol

| Dimensions in mm | Backrest: | H: | 520 |
|------------------|-----------|--------------|---------|
| | Seat: | H: | 400-525 |
| | | W: | 500 |
| | | D: | 520 |
| | Total: | H: | 1140 |
| | | W (no ArmR): | 545 |
| | | W (ArmR): | 600 |
| | | D: | 610 |
| Packaging data | Weight: | kg | 19,5 |
| | Volume: | m³ | 0,65 |
| | | | |



| Options | | Benefit |
|--------------------------|---|--|
| Castors | Soft castors, load-dependent braked, for hard floors (acc. to DIN EN 12529) or glides (soft/hard). | The chair does not roll away in an off-loaded situation, minimum risk of accident. |
| Base | Aluminium base, anthracite, chromed or aluminium polished. | Very high stability, longevity. |
| Nechanical sprung column | Also in the lowest seating position. | Damping of an excessive vertical impact, so that the spine will be preserved. |
| .umbar support | Depth adjustable lumbar support. | Through a mechanical pushing the lumbar support which is integrated in the back upholstery will be adjusted horizontally and will be adapted to the corporal conditions of the user. In that way an individual support in the lumbar area is possible. |
| Armrest | Aluminium ring arm rests with or witouth leather pads, polished or chromed. 3D Auto Flow arm rests, adj. in height (100 mm) & width (460 - 530 mm), soft. 3D T-arm rests, adj. in height (100 mm) & width (450 - 520 mm), depth (60 mm), soft. | The armrests relieve the neck and shoulder muscles. |
| <i>N</i> aterial | Several fabric collections are available in different colours. | During the design of the chair several colours and upholstery materials are available. |
| Accessories | Coat hanger, polypropylene black. | |

Disassembly instructions are available upon request for any interstuhl product