

Technical data sheet 5C35

Specification Cantilever frame, medium, armrests

| | | | | |
|------------------|----------------|---------|-----------|-----|
| Dimensions in mm | Backrest: | H: | 470 | |
| | | Seat: | H: 420 | |
| | Total: | W: | 480 | |
| | | D: | 470 | |
| | | H: | 900 | |
| | Packaging data | Weight: | kg | 10 |
| | | | W (ArmR): | 605 |
| D: | | | 600 | |
| Packaging data | Volume: | m³ | 0,3 | |



Basic equipment

Benefit

| | | |
|---------------------|---|--|
| Backrest | Membrane covered. | Seating comfort through ergonomically designed backrest. |
| Upholstery | Seat upholstery: 50 mm Backrest. Seat cover fabric fastened with drawstring, backrest by sack method and zipper, upholstered without glue. Breathable moulded foam, CFC and CHC-free (pure foam). | Optimum microclimate through unglued upholstery, breathable. Good seating comfort. |
| Frame | Cantilever model, tubular steel frame, powder-coated black. | High stability, long service life. Coating against scratches, etc. |
| Seat support | Plastic. | Sturdy mounting base for the frame. |
| Plastic parts | Dye penetration, thus "colourfast" even with deep scratches and scars. | Very hard wearing. |
| Armrests | Black plastic. | Armrests take the strain off the neck muscles. |
| Materials | All materials are pure and recyclable. | Environmentally friendly. Spares resources. |
| Standards | DIN 16139 four legged and cantilever models. GS-Symbol for tested safety, tested for contaminants. Bifma tested. | High safety and comfort. |
| Certification | Quality management system DIN EN ISO 9001:2008, VO (EG) No. 1221/2009 (EMAS), environmental management system DIN EN ISO 14001:2009, OHSAS, EcoVadis gold, Commitment to sustainability. Quality Office, Blue Angel, Bifma e3 level Platin. | High-quality product. |
| Warranty and return | 10 years warranty. Full return and recycling warranty. | High safety and long service life by minimising costs. |

Disassembly instructions are available upon request for any interstuhl product

Technical data sheet 5C35

Specification Cantilever frame, medium, armrests

| | | | |
|------------------|-----------|-----------|-----|
| Dimensions in mm | Backrest: | H: | 470 |
| | | H: | 420 |
| | Seat: | W: | 480 |
| | | D: | 470 |
| | Total: | H: | 900 |
| | | W (ArmR): | 605 |
| Packaging data | Weight: | kg | 10 |
| | Volume: | m³ | 0,3 |



Options

Benefit

| | | |
|--------|------------------------------|---|
| Glides | Felt glides for hard floors. | Optimum stability of the chair. Spares the floor. |
|--------|------------------------------|---|

| | | |
|------------------|---|--|
| Fabric materials | Several fabric qualities and leather in various colours and two membrane colours. | A wealth of possibilities to design the chair. |
|------------------|---|--|

| | | |
|-------|---|---|
| Frame | Cantilever model, tubular steel frame, chromed or brilliant silver. | Very high stability, long service life High-quality look. |
|-------|---|---|

| | | |
|----------|--------------------------------|--|
| Armrests | Armrests covered with leather. | |
|----------|--------------------------------|--|

Disassembly instructions are available upon request for any interstuhl product