

## **Technical data sheet JC217**

Specification Swivel armchair high, mesh, Synchron, FlexGrid

Dimensions in mm	Backrest:	H:	665
	Seat:	H:	420-530
		W:	500
		D:	460
	Total:	H:	1240
		W (no ArmR):	500
		W (ArmR):	725
		D:	630
Packaging data	Weight:	kg	16,7
	Volume:	m³	0,7



Basic equipment		Benefit
Plastic parts	Colour maintained throughout, black, light grey.	Colourfast and resistant to deep scratches and abrasions.
Backrest	Backrest high, mesh-covered, black.	
Upholstery	Seat upholstery: 55 mm foam, upholstery is unglued, ensuring optimal air movement, breathable.	Great seating comfort.
Mechanism	Synchronous mechanism. Large opening angle between the seat and the backrest of up to 118°.	Synchronous mechanisms of Interstuhl are designed in a way that they help to support optimally the body in every seating position and at the same time they relieve the chang between the different seating positions.
Seat height adjustment	Seat height adjustment infinitely variable from 410 - 520 mm. Self-supporting safety gas spring.	Even people outside the DIN range (i.e. taller than 192cm and smaller than 151cm) will sit in the most ergonomic way.
Weight Adjustment	From 45 - 120 kg, adjustable within 7 steps.	Individual adjustment of the backrest and the back pressure to the weight and height of the user.
Seat depth adjustment	Individual adjustment of the seat depth, 60 mm adjustment.	
Lumbar support	Adjustable height and depth.	Through to a mechanical rotation, the depth of the FlexGrid integrated into the back frame can be adjusted (and the height can be adjusted simply by moving it) and adapted to the anatomical build of the person sitting in the chair. This provides custom support in the lumbar spine area.
Castors Ø 65 mm	Hard double castors, black, load dependent braked, for soft floors. (Acc. to DIN EN 12529).	The chair does not roll away in an off-loaded situation, minimum risk of accident.
Base	Colour maintained throughout polyamide base, black.	Colourfast and resistant to deep scratches and abrasions.
Chair column	Column colour matches the base colour.	Uniform colour scheme for the whole model.
Materials	All materials are segregated and recyclable.	Environmentally friendly.



## **Technical data sheet JC217**

Specification Swivel armchair high, mesh, Synchron, FlexGrid

Dimensions in mm	Backrest:	H:	665	
	Seat:	H:	420-530	
		W:	500	
		D:	460	
	Total:	H:	1240	
		W (no ArmR):	500	
		W (ArmR):	725	
		D:	630	
Packaging data	Weight:	kg	16,7	
0 0	Volume:	m³	0,7	
Standards			ce swivel chairs and office swivel	High quality product and great comfort.
			Symobl for tested safety, tested s, Ergonomics approved.	
Certification			ment system DIN EN ISO	High quality product.
			(EG) No. 1221/2009 (EMAS), nanagement system DIN EN	
			, OHSAS, EcoVadis gold,	
		Commitment to	sustainability. Quality Office.	
Warranty and return		•	ty. Complete return and	Exchange of parts free of charge within the guaranteed
		recycling guaran	itee.	period.

Disassembly instructions are available upon request for any interstuhl product



## **Technical data sheet JC217**

Specification Swivel armchair high, mesh, Synchron,FlexGrid

Dimensions in mm	Backrest:	H:	665
	Seat:	H:	420-530
		W:	500
		D:	460
	Total:	H:	1240
		W (no ArmR):	500
		W (ArmR):	725
		D:	630
Packaging data	Weight:	kg	16,7
	Volume:	m³	0,7



Options		Benefit
Castors	Soft double castors, load dependent braked, for hard floors (Acc. to DIN EN 12529).	The chair does not roll away in an off-loaded position, minimum risk of accident.
Base	Polished aluminium and light-grey plastic	Very high stability, long service life. High-quality look.
Seat inclination	Adjustment of seat +4,9°	The inclination prevents the pelvis from tilting to the reat, ensures the right position of the spinal column.
Armrests	2D T-armrests, adjustable height/width. 3D T-armrests, adjustable height/width/depth, soft. 4D T-armrests, adjustable height/width/depth, rotatable, soft.	The armrests relieve the neck and shoulder muscles.
Cover materials	Various fabric and leather options available.	Individual design.

Disassembly instructions are available upon request for any interstuhl product